

**36-50 kW**



	SODIUM METAL CHLORIDE BATTERY uuZ		WIDE RANGE PZP r		100% UNBALANCE Support Unbalance Load		Max. 1.5 uWK		Max. 40A P		<10 ms ZuDu		INPUT
					uK								

■ Technical Data		AP-E-P3-36K	AP-E-P3-40K	AP-E-P3-50K
PV Input				
DWlt	54	60		75
DWP		1000		
ZP		620		
PZP		150-1000		
DWWPZP		150-850		
DWWZP		500-850		
rP		160		
D		40 4		
DZ		48 4		
EDWWIIP				
<b>W</b>				
EuP		500		
PZP		150-800		
DZP/ZP		120		
DZP/ZPWlt	36	40	50	
ZPP		P		
<b>u</b>				
E	36	40	50	
EP		230 400		
E		50 60		
1	- -			
9		<3%		
E	36000	44000	55000	
EP		230 400		
E		50 60		
E		58		
P		3 %		
		<10		
	9	98 30%	98 30%	
D		%		
ZPIZP		99 00%		
<b>W</b>				
ZWW				
KIPW				
rPW				
ZrW				
IP				
DP				
DP				
<b>W</b>				
General Data			IP65	
utUuu	979	610	310	
tPZIP			IP	
P				
P		I P		
Zu		0-100%		
KPuZP		-25 60 °C		
KPu		<4000		
ut		<100		
uu	4	8 C E-	P 4	
EMC	E E E	EE1 000-6-2 EE 1000-6-3		